

Multi-Grammars

Jiří Techet Tomáš Masopust Alexander Meduna

Department of Information Systems
Faculty of Information Technology
Brno University of Technology
Božetěchova 2, Brno 61266, Czech Republic

Modern Formal Language Theory, 2007

Multisequential Grammar

Multisequential Grammar

$$G = (V, T, P, S, K)$$

where

V, T, S are defined as usual

K is a finite set of **selectors** of the form

$$X_1 \text{ act}(Y_1) \dots X_n \text{ act}(Y_n) X_{n+1}$$

where $n \geq 1$,

$$X_i \in \{Z^* : Z \subseteq V\}, Y_j \in \{Z : Z \subseteq V, Z \neq \emptyset\},$$

$i = 1, \dots, n+1$, and $j = 1, \dots, n$

P is a finite set of productions of the form $a \rightarrow x$, where $a \in V$,
 $x \in V^*$

Multisequential Grammar – Derivation Step

Direct Derivation

If there is

$$X_1 \text{ act}(Y_1) \dots X_n \text{ act}(Y_n) X_{n+1} \in K$$

satisfying

1 $u_i \in X_i$, for all $i = 1, \dots, n + 1$,

2 $a_j \in Y_j$ and

3 $a_j \rightarrow x_j \in P$,

for all $j = 1, \dots, n$, then

$$u_1 a_1 \dots u_n a_n u_{n+1} \Rightarrow u_1 x_1 \dots u_n x_n u_{n+1}$$

Note

The generated language and \Rightarrow^* are defined as usual

Multisequential Grammar – Example

Example

$$G = (\{S, a, b, c\}, \{a, b, c\}, P, S, K)$$

where

$$P = \{S \rightarrow abc, \\ a \rightarrow aa, \\ b \rightarrow bb, \\ c \rightarrow cc\}$$

and

$$K = \{\text{act}(\{S\}), \\ \{a\}^* \text{act}(\{a\}) \{b\}^* \text{act}(\{b\}) \{c\}^* \text{act}(\{c\})\}$$

$$L(G) = \{a^n b^n c^n : n \geq 1\}$$

Multisequential Grammar – Generative Power

Generative Power

$$\mathcal{L}(MS) = \mathcal{L}(RE)$$

Descriptive Complexity

Every recursively enumerable language is generated by a multisequential grammar containing **2 nonterminals** and **2 selectors**.

Multicontinuous Grammar

Multicontinuous Grammar

$$G = (V, T, P, S, K)$$

where

V, T, S are defined as usual

K is a finite set of selectors of the form

$$X_1 \text{ act}(Y_1)X_2 \dots X_n \text{ act}(Y_n)X_{n+1}$$

where $n \geq 1$,

$$X_i \in \{Z^* : Z \subseteq V\}, Y_j \in \{Z^+ : Z \subseteq V, Z \neq \emptyset\},$$

$i = 1, \dots, n+1$, and $j = 1, \dots, n$

P is a finite set of productions of the form $a \rightarrow x$, where $a \in V$,
 $x \in V^*$

Multicontinuous Grammar – Derivation Step

Direct Derivation

If there is

$$X_1 \text{ act}(Y_1) \dots X_n \text{ act}(Y_n) X_{n+1} \in K$$

satisfying

- 1 $u_i \in X_i$, for all $i = 1, \dots, n + 1$,
- 2 $y_j \in Y_j$ and
- 3 $y_j = y_{j_1} \dots y_{j_{m_j}}$, $z_j = z_{j_1} \dots z_{j_{m_j}}$, where $y_{j_1} \rightarrow z_{j_1}, \dots, y_{j_{m_j}} \rightarrow z_{j_{m_j}} \in P$
for some $m_j \geq 1$,

for all $j = 1, \dots, n$, then

$$u_1 y_1 \dots u_n y_n u_{n+1} \Rightarrow u_1 z_1 \dots u_n z_n u_{n+1}$$

Note

The generated language and \Rightarrow^* are defined as usual

Example

$$G = (\{S, a, b, c\}, \{a, b, c\}, P, S, K)$$

where

$$P = \{S \rightarrow abc, \\ a \rightarrow aa, \\ b \rightarrow bb, \\ c \rightarrow cc\}$$

and

$$K = \{\text{act}(\{S\}^+), \\ \text{act}(\{a\}^+) \text{act}(\{b\}^+) \text{act}(\{c\}^+)\}$$

$$L(G) = \{a^{2^n} b^{2^n} c^{2^n} : n \geq 0\}$$

Multicontinuous Grammar – Generative Power

Generative Power

$$\mathcal{L}(MC) = \mathcal{L}(RE)$$

Descriptonal Complexity

Every recursively enumerable language is generated by a multicontinuous grammar containing **3 nonterminals** and **2 selectors**.

Multiparallel Grammar

$$G = (V, T, P, S, K)$$

where

V, T, S are defined as usual

K is a finite set of selectors of the form

$$F_1 F_2 \dots F_m$$

where

$$F_j \in \{W^+ : W \subseteq V, W \neq \emptyset\},$$

$j = 1, \dots, m$, for some $m \geq 1$

P is a finite set of productions of the form $a \rightarrow x$, where $a \in V$,
 $x \in V^*$

Multiparallel Grammar – Derivation Step

Direct Derivation

If there is

$$\pi \in K$$

satisfying

- 1 **either** $u = S$ and $S \rightarrow v \in P$,
- 2 **or** there is $k \geq 1$ so that
 - $u = a_1 \dots a_k$, where $a_i \in V$,
 - $u \in \pi$,
 - $v = x_1 \dots x_k$ and $a_i \rightarrow x_i \in P$

for all $i = 1, \dots, k$, then

$$u \Rightarrow v$$

Note

The generated language and \Rightarrow^* are defined as usual

Example

$$G = (\{S, A, B, C, a, b, c\}, \{a, b, c\}, P, S, K)$$

where

$$P = \{S \rightarrow aAbBcC, \quad S \rightarrow abc, \\ A \rightarrow aA, \quad A \rightarrow a, \quad a \rightarrow a, \\ B \rightarrow bB, \quad B \rightarrow b, \quad b \rightarrow b, \\ C \rightarrow cC, \quad C \rightarrow c, \quad c \rightarrow c\}$$

and

$$K = \{a\}^+ \{A\}^+ \{b\}^+ \{B\}^+ \{c\}^+ \{C\}^+$$

$$L(G) = \{a^n b^n c^n : n \geq 1\}$$

Generative Power

$$\mathcal{L}(MP) = \mathcal{L}(RE)$$

Descriptive Complexity

Every recursively enumerable language is generated by a multiparallel grammar containing **7 nonterminals** and **4 selectors** of the **length 5** ($m = 5$).



H. C. M. Kleijn and G. Rozenberg.

Multi grammars.

International Journal of Computer Mathematics, 12:177–201, 1983.



T. Masopust.

Regulated Formal Models and Their Reductions.

PhD thesis, Faculty of Information Technology, Brno University of Technology, Brno, Czech Republic, 2007.